



EXPORT FUEL ✓


GULF OIL
MATERIAL SAFETY DATA SHEET

GULF MP GL-5 GEAR LUBRICANT, SAE 85W-140

PAGE 1

Product Code: 332106

NFPA HAZARD RATING
4 - Extreme
3 - High
2 - Moderate
1 - Slight
0 - Insignificant



DIVISION AND LOCATION---SECTION I

Division: MASTER DISTRIBUTOR OF GULF LUBRICANTS
Location: AMERICAN REFINING GROUP INC
77 N. KENDALL AVENUE, BRADFORD, PA, 16701
Emergency Telephone Number: 814-368-1297
Transportation Emergency: CHEMTREC 1-(800) 424-9300 (U.S. and Canada)

CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

Chemical Name:
petroleum hydrocarbon plus additives
Formula: not applicable
Hazardous Decomposition Products:
carbon monoxide and carbon dioxide from burning.
oxides of phosphorous from burning
oxides of sulfur
Incompatibility (Keep away from):
strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.
Toxic and Hazardous Ingredients:
none
Form: liquid
Appearance: viscous liquid
Specific Gravity (water=1):
Boiling Point: greater than 330°C (625°F)
Melting Point: +5F(-15C)max
Solubility in Water (by weight %): 0 at 20°C
Volatile (by weight %): 0
Evaporation Rate: 0
Vapor Pressure (mm Hg at 20°C): 0
Vapor Density (air=1): not volatile
pH (as is): not applicable
Stability: Product is stable under normal conditions
Viscosity SUS at 100°F: Greater than or = to 100

Odor: pungent, sulfur type
Color: green to brown
.87 to .91

(Continued on next page)



GULF OIL
MATERIAL SAFETY DATA SHEET

GULF MP GL-5 GEAR LUBRICANT, SAE 85W-140

PAGE 2

Product Code: 332106

FIRE AND EXPLOSION DATA---SECTION III

Special Fire Fighting Procedures:

Do not use water except as fog.

Unusual Fire and Explosion Hazards:

Do not cut, weld, braze, solder, drill, grind or expose containers, drums, tanks, etc. of product to heat, flame, sparks, static electricity or other sources of ignition; they may ignite explosively.

Flashpoint: (Method Used) Cleveland open cup greater than 260°C (500°F)

Flammable limits % : not applicable

Extinguishing agents:

Drychemical or Waterfog or CO₂ or Foam

Closed containers exposed to fire may be cooled with water.

HEALTH HAZARD DATA---SECTION IV

Permissible concentrations (air):

If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m³ for mineral oil mist (OSHA and ACGIH).

Chronic effects of overexposure: Prolonged or repeated skin contact may cause dermatitis (skin irritation)

Acute toxicological properties: no data available

Emergency First Aid Procedures:

Eyes: Immediately flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation: Remove victim to fresh air. Call a physician.

If Swallowed: Contact a physician immediately.

SPECIAL PROTECTION INFORMATION---SECTION V

Ventilation Type Required (Local, mechanical, special):

Local if necessary to maintain allowable PEL(permissible exposure limit) or TLV(threshold limit value)

Respiratory Protection (Specify type): Use NIOSH/MSHA certified respirator with dual organic vapor/mist and particulates cartridge if vapor concentration exceeds permissible exposure limit.

Protective Gloves: neoprene type

Eve Protection:

chemical safety goggles

Other Protective Equipment: none

(Continued on next page)



GULF OIL
MATERIAL SAFETY DATA SHEET

GULF MP GL-5 GEAR LUBRICANT, SAE 85W-140

PAGE 3
Product Code: 332106

HANDLING OF SPILLS OR LEAKS---SECTION VI

Procedures for Clean-Up: Transfer bulk of mixture into another container. Absorb residue with an inert material such as earth, sand, or vermiculite. Sweep up and dispose as solid waste in accordance with local, state, and federal regulations.

Waste Disposal: Dispose of in accordance with all applicable federal, state and local regulations.

SPECIAL PRECAUTIONS---SECTION VII

Precautions to be taken in handling and storage:

Do not handle or store at temperatures over
Maximum Storage Temperature: 60 ° C (140 ° F)

TRANSPORTATION DATA---SECTION VIII

H. O. T. : Not Regulated

Reportable Quantity : not applicable

Light Classification: Petroleum Lubricating Oil

Special Transportation Notes: none

ENVIRONMENTAL/SAFETY REGULATIONS---SECTION IX

Section 313 (Title III Superfund Amendment and Reauthorization Act):

This product does not contain any chemical in sufficient quantity to be subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

COMMENTS

The additive mixtures in this product have been declared a trade secret by the additive manufacturers.

(Continued on next page)



GULF OIL
MATERIAL SAFETY DATA SHEET

GULF MP GL-5 GEAR LUBRICANT, SAE 85W-140

Product Code: 332106

PAGE 4

(COMMENTS continued)

Prepared by: R. M. KELLAM

Title: PRODUCT SAFETY & HEALTH COORDINATOR

Original Date: 06/15/98 Sent to:

Revision Date: 02/14/00

Supersedes: 06/15/98

Date Sent

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.